

## CH4(메탄) 센서 모듈, 트랜스미터, 플로우 타입

가스종류	모델명	구성센서	제품사진	제품타입	센서 원리	측정범위	주 용도, 특징	입력전원	감도	검출한계	정확도	출력	옵션 주문사항	크기
CH4	CH4-D3-3V	CH4		듀얼모듈	NDIR	0~100% LEL (0~ 50000ppm)	누출 감지	3.3V	1% LEL (500 ppm)	2% LEL (1000 ppm)	F.S. 3%	UART, I2C, Alarm	5 V 구동용, 슬립 모드, 방수코팅, Aout, PWM 출 력	33mm× 33mm× 13.1mm (L,D,H)
CH4	CH4-S3-3V	CH4		싱글모듈	NDIR	0~100% LEL (0~ 50000ppm)	누출 감지	3.3V	1% LEL (500 ppm)	2% LEL (1000 ppm)	F.S. 3%	UART, I2C, Alarm	5 V 구동용, 슬립 모드, 방수코팅, Aout, PWM 출 력	33mm× 33mm× 13.1mm (L,D,H)
CH4	CH4-K100D (CH4-K100F)	CH4		싱글모듈	NDIR	0~5000ppm (0~50000 가능)	누출 감지	12VDC	20ppm	F.S. 1%	F.S. 3%	UART, I2C, Analog, RS485 (옵션)	온습도 선택, 공기유입방법선택 (확산D, 강제유 입F)	76mmx 64mmx 22mm (L,D,H)
CH4	CH4-CD300	CH4 모듈탑재		트랜스미터	NDIR	0~100% LEL (0~ 50000ppm)	메탄농도 측정, 정확성우수, 안정성	24V DC	1% LEL (500 ppm)	2% LEL (1000 ppm)	F.S. 3%	3선, 4(0)~20mA, 0(2)~10V	LCD 장착 가능 방수코팅	123mm x 70mm x 43mm (L,D,H)
CH4	CH4-CD400	CH4 모듈탑재		트랜스미터	NDIR	0~100% LEL (0~ 50000ppm)	메탄농도 측정, 정확성우수, 안정성	24V DC	1% LEL (500 ppm)	2% LEL (1000 ppm)	F.S. 3%	릴레이, 4(0)~20mA, 0(2)~10V, 0(1)~5V	LCD 장착 가능 방수코팅	123mm x 70mm x 43mm (L,D,H)
CH4	CH4-S3-PF	CH4-S3 모듈탑 재 (0~ 50000ppm)		플로우 타입	NDIR	0~100% LEL (0~50000 ppm)	흡입식, 산업용	5V	1% LEL	2% LEL	F.S. 3%	UART, I2C,PWM,Alarm, Analog 선택1	3.3 v 구동용 주 문가능	58mm x 59.4mm x 26mm (L,D,H)
CH4	CH4-D3-PF	CH4-D3 모듈탑 재 (0~ 50000ppm)		플로우 타입	NDIR	0~100% LEL (0~50000 ppm)	흡입식, 산업용	5V	1% LEL	2% LEL	F.S. 3%	UART, I2C,PWM,Alarm, Analog 선택1	3.3 v 구동용 주 문가능	58mm x 59.4mm x 26mm (L,D,H)